

## RIG SPECIFICATIONS >> CME 75 (LN 9000 Ford 4WD Truck)

Our Truck-Mounted rigs provide easy mobilization & access to project sites.



- Four Wheel Drive Truck (Ford LN 9000)
- Truck Mounted Drill (Fully Loaded): 32,000 lbs
- Drill Power: 6 Cylinder Ford Industrial Diesel Engine
- Drill Rig Rotary Capacity: 3 – 6 inch diameter, 100 – 500 ft depth
- Drill Rig Auger Capacity: 4 – 12 inch diameter, 100 – 300 ft depth
- Drill Set-up Working Height: 28 feet
- Drill Mast-Down Height: 11 feet
- Drill Head Rotational Speeds: 55-620 RPM
- Water Pump: John Bean 35
- Main Winch Capacity: 7000 lbs
- Drill Head Capacity: 20,000 lbs down, 30,000 lbs up
- Spindle Torque: Maximum 13,000 lbs
- Drill Cathead: 8 inch, 3 speeds
- Safety Sample Hammer: 140 lbs, 30 inch drop
- Automatic Standard Penetration Hammer available

TABER DRILLING

TEL 916.371.1690  
FAX 916.371.7265  
TOLL FREE 888.423.0573

[www.taberdrilling.com](http://www.taberdrilling.com)

