

RIG SPECIFICATIONS >> CME 300 - 55 - Track Mounted



The newest addition to our drilling fleet is the track mounted CME-55 rig. This rig provides easy mobilization and access to project sites during extreme winter months and conditions for drilling or In-Situ Testing (CPT). Taber is one of three companies in the state to have a track mounted rig available for In-Situ Testing.



- Rubber Tracked CME 300 Carrier
- Carrier Dimensions: 7-Ft 3-In Wide by 13-Ft 2-In Long
- Mast to Ground Height: Down, 8-Ft 6-In, Up, 25-Ft
- Steering: Remote Radio Controlled
- Gradeability: Straight Ahead – 50%, Side Hill – 36%
- Drill Power: Cummins 4BT 3.9 Diesel Engine
- GVW: Carrier and Rig - 15,000 Pounds
- Ground Bearing Pressure: 4.5 PSI
- Rotary Torque: 9842 Foot Pounds
- Pull Down: 18,650 Pounds
- Retract Force: 28,275 Pounds
- Angle Drilling Capable with Telescoping Stabilizers
- Water Pump: John Bean 35
- Cathead and Safety Hammer: 140 Pounds, 30-Inch Drop
- Main Winch Hoist Capacity: 7000 Pounds
- Drill Rotary Capacity: 3 - 6 Inch Diameter, 100 - 500 Foot Depth
- Drill Auger Capacity: 4 - 12 Inch Diameter, 100 - 200 Foot Depth
- Automatic Standard Penetration Hammer Available

TABER DRILLING

TEL 916.371.1690
FAX 916.371.7265
TOLL FREE 888.423.0573

www.taberdrilling.com



3911 West Capitol Avenue
West Sacramento, California 95691-2116