

RIG SPECIFICATIONS >> CME 45-B (F-700 Ford Truck)

Our truck mounted rigs provide easy mobilization and access to project sites.



- Truck Mounted Drill (Fully Loaded): 22,000 lbs
- Drill Power: 4 cylinder, 163 cubic inch industrial gas engine
- Drill Rig Rotary Capacity: 2 - 4 inch diameter, 150-250 ft depth
- Drill Rig Auger Capacity: 3 - 12 inch diameter 75-150 ft depth
- Drill Set-up Working Height: 29 feet
- Drill Mast-Down Height: 11 feet
- Drill Head Rotational Speeds: 118-745 RPM
- Water Pump: John Bean 25
- Winch Capacity: 1800 lbs at ± 200 l.f. / minute
- Drill Head Capacity: 9000 lbs down, 12,000 lbs up
- Drill Cathead: 8 inch, 3 speeds
- Safety Sample Hammer: 140 lbs, 30 inch drop
- Drill Capable of Diamond Coring, Wireline Drilling and Air Drilling
- McKiernan Terry air driven Cone Penetration Test Hammer available as supplemental CME-45B capability

TABER DRILLING

TEL 916.371.1690
FAX 916.371.7265
TOLL FREE 888.423.0573

www.taberdrilling.com

