

RIG SPECIFICATIONS >> SIMCO 2400 HT (High Torque)

Our crawler-mounted rigs provide easy mobilization & access to project sites.



- Rubber Track ATV Carrier (Chickusui GC-640)
- Indoor or Outdoor Use: Track Ground Pressure @ 3.7 psi
- Angle Drilling Capable
- Drill and Crawler Weight: 4,500 lbs (With Bean Pump)
- Drill and Crawler Length: 11.20 ft
- Drill and Crawler Width: 3.75 ft
(Can be reduced to 3.50 ft upon request)
- Drill and Crawler Height: Mast Down 6.25 ft
Mast Up 11.25 ft
Tall Mast Up 15.6 ft
- Drill Power: 30 HP Air Cooled Engine
- Water Pump: John Bean 25
- Cathead and Safety Sample Hammer: 140 lbs, 30 inch drop
- Winch Hoist Capacity: 1800 lbs
- Drill Rig Rotary Capacity: 3 - 4 inches diameter, 100 to 120 ft
- Drill Rig Auger Capacity: 4 - 8 inches diameter, 80 to 100 ft
- Drill Capable of Diamond Coring, Wireline Drilling and Air Drilling

TABER DRILLING

TEL 916.371.1690
FAX 916.371.7265
TOLL FREE 888.423.0573

www.taberdrilling.com

